



TiForged Air High Frame Spinning Guide Kit

Spacing measured in inches from tip top ring to guide ring, starting from the tip.

Rod Length	Rear Grip Length*	1	2	3	4	5	6	7	8	9	10
6'0"	6"	3"	6 1/2"	10 1/2"	14 7/8"	20 1/2"	26 1/2"	34 1/8"	42 5/8"		
6'3"	6"	3"	6 1/2"	10 1/2"	14 7/8"	19 5/8"	24 5/8"	30 1/8"	37 1/8"	45 5/8"	
6'6"	7"	3"	6 1/2"	9 7/8"	13 5/8"	17 7/8"	22 5/8"	27 3/4"	33 1/8"	40 1/4"	48 1/2"
6'9"	8"	3"	6 1/2"	9 7/8"	13 5/8"	17 7/8"	23"	29 1/4"	37 5/8"	47"	
6'10"	8"	3"	6 1/2"	9 7/8"	13 5/8"	17 7/8"	23 3/8"	30 1/8"	38 1/2"	48 1/8"	
7'0"	9"	3"	6 1/2"	9 7/8"	13 5/8"	18 1/8"	24"	30 7/8"	39 1/4"	49 1/8"	
7'2"	9"	3"	6 1/2"	9 7/8"	13 5/8"	17 5/8"	21 7/8"	26 3/4"	33 1/8"	41 1/4"	51 1/8"
7'3"	9"	3"	6 1/2"	9 7/8"	13 5/8"	17 7/8"	22 3/8"	27 7/8"	34"	42 1/4"	52 1/8"
7'4"	10"	3"	6 1/2"	9 7/8"	13 5/8"	17 7/8"	22 3/8"	27 7/8"	33 7/8"	42"	52"
7'6"	10"	3 1/8"	6 3/8"	10"	13 3/4"	18 1/8"	23"	28 7/8"	36"	44"	54"
7'9"	10"	3 3/8"	7 1/8"	11 5/8"	16 3/4"	22 1/2"	29 1/8"	36 7/8"	45 5/8"	56 1/8"	
7'11"	10"	3 1/2"	7 1/2"	12"	17 3/4"	24"	31 1/8"	38 7/8"	47 5/8"	58 1/8"	
8'0"	11"	3 1/2"	7 1/2"	12"	17 3/4"	24"	31 1/8"	38 7/8"	47 5/8"	58 1/8"	

*Rear Grip Length is measured from the butt to the rear edge of the reel seat.

The guide spacing shown in this chart is a general recommendation suitable for many applications. However, you may need to adjust it slightly to better fit your specific rod blank and application needs.

AMERICANTACKLE.US