



# Heavy Duty Spinning Guide Kit Spacing - 40 to 80 Lb

Spacing measured in inches from tip top ring to guide ring, starting from the tip.

Model #	Rod Length	1	2	3	4	5	6	7	8	9	10	11
HDSGK-VH-70-8-B	6'	4"	8-1/2"	12-3/4"	17-1/2"	22-3/4"	29-1/4"	36-3/4"				
	6'6"	4"	8-1/4"	12-3/4"	17-4/4"	23-1/2"	31"	40-1/4"				
	7'	4"	8-1/4"	12-5/8"	17-1/4"	22"	27-3/4"	35"	44-1/4"			
HDSGK-VH-90-8-B	7'6"	4"	8"	12-1/4"	16-1/2"	21"	26"	31-3/4"	39"	48-1/2"		
	8'	4 3/8"	8-5/8"	13-1/2"	18-5/8"	24-3/4"	33"	41"	51-1/4"			
	8'6"	4 1/4"	8-1/2"	13-1/4"	18-3/8"	23-3/4"	29-5/8"	37"	45-3/4"	56-1/4"		
	9'	4 1/4"	8-1/2"	13-1/4"	18-3/8"	23-3/4"	29-1/2"	35-1/2"	43"	51-3/4"	62-1/4"	
HDSGK-VH-70-10-B	6'	4"	8-1/2"	12-3/4"	17-1/2"	22-3/4"	29-1/4"	36-3/4"				
	6'6"	4"	8-1/4"	12-3/4"	17-4/4"	23-1/2"	31"	40-1/4"				
	7'	4"	8-1/4"	12-5/8"	17-1/4"	22"	27-3/4"	35"	44-1/4"			
HDSGK-VH-90-10-B	7'6"	4"	8"	12-1/4"	16-1/2"	21"	26"	31-3/4"	39"	48-1/2"		
	8'	4 3/8"	8-5/8"	13-1/2"	18-5/8"	24-3/4"	33"	41"	51-1/4"			
	8'6"	4 1/4"	8-1/2"	13-1/4"	18-3/8"	23-3/4"	29-5/8"	37"	45-3/4"	56-1/4"		
	9'	4 1/4"	8-1/2"	13-1/4"	18-3/8"	23-3/4"	29-1/2"	35-1/2"	43"	51-3/4"	62-1/4"	

\*Rear Grip Length is measured from the butt to the rear edge of the reel seat.

The guide spacing shown in this chart is a general recommendation suitable for many applications. However, you may need to adjust it slightly to better fit your specific rod blank and application needs.