



Heavy Duty Conventional Guide Kit Spacing - 20 to 60 Lb

Spacing measured in inches from tip top ring to guide ring, starting from the tip.

Model #	Rod Length	1	2	3	4	5	6	7	8	9	10	11
HDCGK-VL-66-8-B	5'6"	4"	8 1/4"	12 3/4"	18"	24 1/4"	32"					
	6'	4"	8 1/4"	12 3/4"	18"	23 7/8"	30 1/2"	38"				
	6'6"	4"	8 1/4"	12 3/4"	17 1/2"	23"	29"	36"	44"			
HDCGK-VL-80-8-B	7'	4"	8-1/4"	12-3/4"	17-1/2"	22-3/4"	28-3/8"	34-1/4"	41-1/2"	50"		
	7'6"	4"	8-1/4 "	12-3/4 "	17-1/2 "	22-3/4 "	28-1/4 "	34 "	40-1/2 "	47-5/8"	56"	
	8'	4"	8-1/4 "	12-3/4 "	17-1/2"	22-1/2 "	27-3/4 "	33-1/4 "	39-1/8 "	45-3/4 "	53 "	61-5/8 "
HDCGK-VL-66-10-B	5'6"	4 3/8"	9"	13-3/4 "	19"	25 "	32-1/4 "					
	6'	4 3/8"	9"	13-1/2 "	18-3/4 "	14-1/4 "	30-1/2 "	37-3/4 "				
	6'6"	4 3/8"	9"	13-7/8 "	19 "	24-1/4 "	30 "	36-1/2 "	43-3/4 "			
HDCGK-VL-80-10-B	7'	4 3/8"	9"	13-7/8 "	19 "	24-1/4 "	29-3/4 "	35-7/8 "	42-1/4 "	49-5/8 "		
	7'6"	4 3/8"	9"	13-7/8 "	19 "	24-1/4 "	29-5/8 "	35-5/8 "	41-7/8 "	48-1/4 "	55-3/4 "	
	8'	4 3/8"	9"	13-7/8 "	19 "	24-1/4 "	29-5/8 "	35-5/8 "	41-3/4 "	48 "	54-1/2 "	62 "

*Rear Grip Length is measured from the butt to the rear edge of the reel seat.

The guide spacing shown in this chart is a general recommendation suitable for many applications. However, you may need to adjust it slightly to better fit your specific rod blank and application needs.

AMERICANTACKLE.US