



TiForged Air Spinning Guide Kit Spacing

Spacing measured in inches from tip top ring to guide ring, starting from the tip.

Rod Length	Rear Grip Length*	1	2	3	4	5	6	7	8	9	10	11	12
6'0"	6"	3"	6 3/8"	10 1/2"	14 7/8"	19 1/2"	25 1/4"	32 1/8"	40 1/4"				
6'3"	6"	3"	6 1/2"	10 5/8"	15 1/4"	20 3/4"	27 5/8"	34 7/8"	40 3/8"				
6'6"	7"	3 1/8"	6 3/4"	11"	16"	21 7/8"	28 5/8"	35 7/8"	44 7/16"				
6'9"	8"	3 1/8"	6 3/8"	10"	13 5/8"	17 7/8"	23"	29 5/8"	37 1/4"	46"			
6'10"	8"	3 1/8"	6 3/8"	10"	13 5/8"	18 1/8"	23 7/8"	30 3/8"	38 1/4"	47"			
7'0"	9"	3 1/8"	6 1/4"	9 7/8"	13 5/8"	18 5/8"	24 5/8"	30 5/8"	39 1/4"	48"			
7'2"	9"	3 1/8"	6 1/4"	9 7/8"	14"	19 3/8"	26"	33"	41 1/4"	50"			
7'3"	9"	3 1/8"	6 1/4"	9 7/8"	14 1/4"	19 7/8"	26 7/16"	34"	42 1/4"	51"			
7'4"	10"	3 1/8"	6 1/4"	9 7/8"	13 5/8"	17 1/2"	21 7/8"	27 3/8"	33 7/8"	41 7/8"	51"		
7'6"	10"	3 1/8"	6 1/4"	9 7/8"	13 5/8"	18"	22 7/8"	28 3/4"	35 7/8"	44"	50 7/8"		
7'9"	10"	3 3/8"	7 3/8"	11 7/8"	17 1/2"	23 5/8"	30 1/4"	37 1/4"	45 1/4"	54 1/2"			
7'11"	10"	3 1/2"	7 1/2"	12"	16 1/2"	21 3/8"	26 3/8"	32 5/16"	39 1/4"	47 1/4"	56 5/8"		
8'0"	11"	3 1/2"	7 1/2"	11 3/4"	16 1/4"	21 1/8"	26 3/8"	32 3/8"	39 1/4"	47"	56 1/2"		
8'6"	12"	3 1/2"	7 5/8"	12"	16 3/8"	21"	26"	31 3/8"	37 1/4"	44 1/4"	52 1/4"	61 5/8"	
9'0"	14"	3 1/2"	7 1/4"	11 1/8"	15 1/2"	20 1/2"	25 3/4"	30 7/8"	36 1/4"	41 7/8"	48 5/8"	56 3/8"	65 3/4"

*Rear Grip Length is measured from the butt to the rear edge of the reel seat.

The guide spacing shown in this chart is a general recommendation suitable for many applications. However, you may need to adjust it slightly to better fit your specific rod blank and application needs.

AMERICANTACKLE.US