



Heavy Duty Conventional Guide Kit Spacing - 40 to 80 Lb

Spacing measured in inches from tip top ring to guide ring, starting from the tip.

Model #	Rod Length	1	2	3	4	5	6	7	8	9	10	11
HDCGK-VH-66-8-B	5'6"	4"	8-1/4"	12-3/4"	18"	24-1/4"	32"					
	6'	4"	8-1/4"	12-3/4"	18"	23-7/8"	30-1/2"	38"				
	6'6"	4"	8-1/4"	12-3/4"	17-1/2"	23"	29"	36"	44"			
HDCGK-VH-80-8-B	7'	4"	8-1/4"	12-3/4"	17-1/2"	22-3/4"	28-3/8"	34-1/4"	41-1/2"	50"		
	7'6"	4"	8-1/4"	12-3/4"	17-1/2"	22-3/4"	28-1/4"	34"	40-1/2"	47-5/8"	56"	
	8'	4"	8-1/4"	12-3/4"	17-1/2"	22-1/2"	27-3/4"	33-1/4"	39-1/8"	45-3/4"	53"	61-5/8"
HDCGK-VH-66-10-B	5'6"	4 3/8"	9"	13-3/4"	19"	25"	32-1/4"					
	6'	4 3/8"	9"	13-1/2"	18-3/4"	14-1/4"	30-1/2"	37-3/4"				
	6'6"	4 3/8"	9"	13-7/8"	19"	24-1/4"	30"	36-1/2"	43-3/4"			
HDCGK-VH-80-10-B	7'	4 3/8"	9"	13-7/8"	19"	24-1/4"	29-3/4"	35-7/8"	42-1/4"	49-5/8"		
	7'6"	4 3/8"	9"	13-7/8"	19"	24-1/4"	29-5/8"	35-5/8"	41-7/8"	48-1/4"	55-3/4"	
	8'	4 3/8"	9"	13-7/8"	19"	24-1/4"	29-5/8"	35-5/8"	41-3/4"	48"	54-1/2"	62"

*Rear Grip Length is measured from the butt to the rear edge of the reel seat.

The guide spacing shown in this chart is a general recommendation suitable for many applications. However, you may need to adjust it slightly to better fit your specific rod blank and application needs.