



# Heavy Duty Conventional Guide Kit Spacing - 50 to 200 Lb

Spacing measured in inches from tip top ring to guide ring, starting from the tip.

Model #	Rod Length	1	2	3	4	5	6	7	8	9	10	11
HDCGK-VXHD-66-10-B	5'6"	4 3/8"	9 "	13-3/4 "	19 "	25 "	32-1/4"					
	6'	4 3/8"	9 "	13-1/2 "	18-3/4 "	14-1/4 "	30-1/2"	37-3/4"				
	6'6"	4 3/8"	9 "	13-7/8 "	19 "	24-1/4 "	30"	36-1/2"	43-3/4"			
HDCGK-VXHD-80-10-B	7'	4 3/8"	9 "	13-7/8 "	19 "	24-1/4 "	29-3/4"	35-7/8"	42-1/4"	49-5/8"		
	7'6"	4 3/8"	9 "	13-7/8 "	19 "	24-1/4 "	29-5/8"	35-5/8"	41-7/8"	48-1/4"	55-3/4"	
	8'	4 3/8"	9 "	13-7/8 "	19 "	24-1/4 "	29-5/8"	35-5/8"	41-3/4"	48"	54-1/2"	62"
HDCGK-VXHD-66-12-B	5'6"	4 1/2"	9-1/4 "	14-1/4 "	19-1/2 "	25-1/4 "	32-1/4"					
	6'	4 1/2"	9-1/4 "	14-1/4 "	19-1/2 "	25-1/4 "	31-1/8"	38"				
	6'6"	4 1/2"	9-1/4 "	14-1/4 "	19-1/2 "	25 "	30-3/4"	37"	44"			
HDCGK-VXHD-80-12-B	7'	4 1/2"	9-1/4 "	14-1/4 "	19-1/2 "	24-1/2 "	30"	36"	42-1/4"	49-3/4"		
	7'6"	4 1/2"	9-1/4 "	14-1/4 "	19-1/2 "	24-1/2 "	30"	35-3/4"	41-3/4"	48-1/4"	55-1/2"	
	8'	4 1/2"	9-1/4 "	14-1/4 "	19-1/2 "	24-1/2 "	29-3/4"	35-1/8"	40-7/8"	47-1/4"	54"	62"

\*Rear Grip Length is measured from the butt to the rear edge of the reel seat.

The guide spacing shown in this chart is a general recommendation suitable for many applications. However, you may need to adjust it slightly to better fit your specific rod blank and application needs.